


# Sturgeon Self-Cleaning Screens



**MADE IN THE U.S.A.**

MODEL	RATING	FISH SCREEN			CANISTER DIAMETER	BARE OUTLET	RETURN INLET	GPM TO OPERATE	MIN. OPERATING PRESSURE	BRASS BEARING MAX. OPERATING PRESSURE	SEALED BEARING MAX. OPERATING PRESSURE	HEIGHT	WEIGHT
		GPM FOR .4FT. PER SEC.	MAX. GPM	12 MESH									
ST4	350	160	18"	4"	1 1/2"	20	40	65	100	13"	62		
ST6	450	200	20"	6"	1 1/2"	20	40	65	100	13"	73		
ST8	800	290	24"	8"	1 1/2"	20	40	65	100	17 1/2"	99		
ST10	1200	515	32"	10"	1 1/2"	20	40	65	100	17 1/2"	187		
ST12	1800	725	38"	12"	1 1/2"	20	40	65	100	19 1/2"	220		

**REQUIRED** - Filter Strainer On Supply Line To Sturgeon Filter.

**STANDARD** - Galvanized Body With Stainless Steel 12 Mesh Screen - Plain End Outlet

**OPTIONAL** - Stainless Mesh Size - Connection On Sturgeon Outlet - Flanged, King Nipple, Ring Lock, Victaulic, or Water Tight Coupler.  
Sealed Bearing - Operating Range 40 to 100 P.S.I.



Manufacturers and Distributors of Irrigation and Industrial Equipment  
6983 Supply Way • Boise, Idaho 83716  
(208) 345-2525 / Toll Free 1-800-635-5975  
FAX 1-208-345-2143  
www.clemonssales.net  
e-mail purchasing@clemonssales.net